

.079"(2.0mm) Cable Helder

Specifications:


- Current rating: 1A AC, DC
- Voltage rating: 125V AC, DC
- Dielectric withstanding voltage: 500V AC/minute
- Insulation resistance: 1000MΩ Min.
- Contact resistance: 5mΩ Max.
- Ambient temperature range: -25 °C ~ 85 °C (including temperature rise)

20009H-N Series Cable Helder

inches
mm


- 2 ~ 15 circuits available
- Material: UL 94V-0 nylon 66
- Used with discrete wire, flat cable & ribbon cable
- Wire range: #26 ~ #28 AWG
- Applicable P. C. B. thickness: 0.8 ~ 1.6mm

20009HA-N



P. C. board hole dimensions

20009HB-N



P. C. board hole dimensions

Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	0.079 (2.0)	0.283 (7.2)	7	0.472 (12.0)	0.677 (17.2)	12	0.866 (22.0)	1.071 (27.2)
3	0.157 (4.0)	0.362 (9.2)	8	0.551 (14.0)	0.756 (19.2)	13	0.945 (24.0)	1.150 (29.2)
4	0.236 (6.0)	0.441 (11.2)	9	0.630 (16.0)	0.835 (21.2)	14	1.024 (26.0)	1.228 (31.2)
5	0.315 (8.0)	0.520 (13.2)	10	0.709 (18.0)	0.913 (23.2)	15	1.102 (28.0)	1.307 (33.2)
6	0.394 (10.0)	0.598 (15.2)	11	0.787 (20.0)	0.992 (25.2)			