

.098" (2.5mm) Cable Helder

Specifications:


- Current rating: 1A AC, DC
- Voltage rating: 125V AC, DC
- Dielectric withstanding voltage: 800V AC/minute
- Insulation resistance: 1000M Ω Min.
- Contact resistance: 5m Ω Max.
- Ambient temperature range: -25 °C ~ 85 °C max. (including temperature rise)

25012H-N Series Cable Helder

inches
mm


- 2 ~ 20 circuits available
- Material: UL 94V-0 nylon 66
- Used with discrete wire, flat cable & ribbon cable
- Wire range: #24 ~ #26 AWG
- Applicable P. C. B. thickness: 0.8 ~ 1.6mm

25012HA-N



P. C. board hole dimensions

25012HB-N



P. C. board hole dimensions

Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	0.098 (2.5)	0.307 (7.8)	9	0.787 (20.0)	0.996 (25.3)	16	1.476 (37.5)	1.685 (42.8)
3	0.197 (5.0)	0.406 (10.3)	10	0.886 (22.5)	1.094 (27.8)	17	1.575 (40.0)	1.783 (45.3)
4	0.295 (7.5)	0.504 (12.8)	11	0.984 (25.0)	1.193 (30.3)	18	1.673 (42.5)	1.882 (47.8)
5	0.394 (10.0)	0.602 (15.3)	12	1.083 (27.5)	1.291 (32.8)	19	1.772 (45.0)	1.980 (50.3)
6	0.492 (12.5)	0.701 (17.8)	13	1.181 (30.0)	1.390 (35.3)	20	1.870 (47.5)	2.079 (52.8)
7	0.591 (15.0)	0.799 (20.3)	14	1.280 (32.5)	1.488 (37.8)			
8	0.689 (17.5)	0.898 (22.8)	15	1.378 (35.0)	1.587 (40.3)			