


.100"(2.54mm) Crimp Terminal Housing

Specifications:


- Current rating: 3A DC
- Voltage rating: 250V AC, DC
- Insulation resistance: 1000M Ω Min.
- Dielectric withstanding voltage: 800V AC/minute
- Ambient temperature range: -25 °C ~ 85 °C
(including temperature rise)

25406HP-N Series Crimp Terminal Housing

- 6 ~ 72 circuits available
- Material: P.B.T. UL 94V-0
- Accepts 25407TF terminal
- Mates with 25406W headers



inches
mm



Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
6	0.20 (5.08)	0.481 (12.22)	30	1.40 (35.56)	1.681 (42.70)	54	2.60 (66.04)	2.881 (73.18)
8	0.30 (7.62)	0.581 (14.76)	32	1.50 (38.10)	1.781 (45.24)	56	2.70 (68.58)	2.981 (75.72)
10	0.40 (10.16)	0.681 (17.30)	34	1.60 (40.64)	1.881 (47.78)	58	2.80 (71.12)	3.081 (78.26)
12	0.50 (12.70)	0.781 (19.84)	36	1.70 (43.18)	1.981 (50.32)	60	2.90 (73.66)	3.181 (80.80)
14	0.60 (15.24)	0.881 (22.38)	38	1.80 (45.72)	2.081 (52.86)	62	3.00 (76.20)	3.281 (83.34)
16	0.70 (17.78)	0.981 (24.92)	40	1.90 (48.26)	2.181 (55.40)	64	3.10 (78.74)	3.381 (85.88)
18	0.80 (20.32)	1.081 (27.46)	42	2.00 (50.80)	2.281 (57.94)	66	3.20 (81.28)	3.481 (88.42)
20	0.90 (22.86)	1.181 (30.00)	44	2.10 (53.34)	2.381 (60.48)	68	3.30 (83.82)	3.581 (90.96)
22	1.00 (25.40)	1.281 (32.54)	46	2.20 (55.88)	2.481 (63.02)	70	3.40 (86.36)	3.681 (93.50)
24	1.10 (27.94)	1.381 (35.08)	48	2.30 (58.42)	2.581 (65.56)	72	3.50 (88.90)	3.781 (96.04)
26	1.20 (30.48)	1.481 (37.62)	50	2.40 (60.96)	2.681 (68.10)			
28	1.30 (33.02)	1.581 (40.16)	52	2.50 (63.50)	2.781 (70.64)			